



Segrate, 26/03/2018

Based on the data supplied by the builder, Osculati srl certifies that the items:

**AISI316 STAINLESS STEEL WIRE ROPE's
features are the ones listed on the table below**

Part number	Construcion	Diameter (mm)	Actual Measurement Diameter (mm)	Tensile strength Mpa		Breaking strength (KN)	
				Standard	Actual measurement	Standard	Actual measurement
03.171.10	1X19	10	10,1	1570	1570	≥82.4	83,2
03.171.12	1X19	12	12,2	1570	1570	≥118.7	119,6
03.171.15	1X19	1,5	1,52	1570	1570	≥1.85	2,04
13.171.20	1X19	2	2,03	1570	1570	≥3.30	3,56
03.171.25	1X19	2,5	2,52	1570	1570	≥5.15	5,45
03.171.30	1X19	3	3,03	1570	1570	≥7.42	7..69
03.171.40	1X19	4	4,05	1570	1570	≥13.19	14,52
03.171.50	1X19	5	5,05	1570	1570	≥20.61	21,42
.03.171.60	1X19	6	6,08	1570	1570	≥29.67	30,65
03.171.70	1X19	7	7,1	1570	1570	≥40.39	41,98
03.171.80	1X19	8	8,1	1570	1570	≥52.75	53,69

